


# POWERDRIVE AQUADAPT Pipe Flashings



Aquadapt Flashings are specifically designed for use on new as well as retrofit installations without the necessity of dismantling the pipework or duct. Forget the hassle of dismantling rooftop pipe and duct work. Aquadapt flashes existing installations perfectly in seconds and can be formed to the roof profile by hand, without effort. Tough, reliable and so flexible! Ideal for boat masts and other similar installations.

- Products are available in Black EPDM for standard temperature range (-40° to 115°) and Red Silicone for High Temperature. Range (-60° to 240°).
- For applications where the roof pitch exceeds 25° the Aquadapt seam should be placed on the side when installed.



Use Powerdrive RX520HM self-drilling screws to stitch Aquadapt base to metal roof sheeting.

## SIZES & DIMENSION

### AQUADAPT PIPE FLASHINGS – EPDM BLACK



Part No.	Size No.	Base Dimensions mm	PIPE O.D. RANGE		No. of Clips Required*
			0° – 25° Roof Pitch mm	0° – 45° Roof Pitch mm	
AAE1B8-40	1	115 x 115	8 to 50	8 to 40	4
AAE2B10-70	2	155 x 155	10 to 90	10 to 70	5
AAE3B40-90	3	203 x 203	40 to 100	40 to 90	5
AAE4B75-135	4	255 x 255	75 to 150	75 to 135	6
AAE5B125-180	5	305 x 305	125 to 200	125 to 180	6
AAE6B145-230	6	355 x 355	145 to 250	145 to 230	7
AAE7B195-250	7	432 x 432	195 to 300	195 to 250	7
AAE8B230-380	8	540 x 600	230 to 380	230 to 355	9
AAE9B315-450	9	650 x 720	315 to 500	315 to 450	11
AAE10B400-730	10	965 x 995	400 to 750	400 to 630	15


\* Required for retrofit installations only.

### AQUADAPT PIPE FLASHINGS – SILICONE RED



Part No.	Size No.	Base Dimensions mm	PIPE O.D. RANGE		No. of Clips Required*
			0° – 25° Roof Pitch mm	0° – 45° Roof Pitch mm	
AAS2R10-70	2	155 x 155	10 to 90	10 to 70	5
AAS3R40-90	3	203 x 203	40 to 100	40 to 90	5
AAS4R75-135	4	255 x 255	75 to 150	75 to 135	6
AAS5R125-180	5	305 x 305	125 to 200	125 to 180	6
AAS6R145-230	6	355 x 355	145 to 250	145 to 230	7
AAS7R195-250	7	432 x 432	195 to 300	195 to 250	7
AAS8R230-380	8	540 x 600	230 to 380	230 to 355	9
AAS9R315-450	9	650 x 720	315 to 500	315 to 450	11
AAS10R400-730	10	965 x 995	400 to 750	400 to 630	15

\* Required for retrofit installations only.



Retrofit Clips  
Part No. SSC01/50

## Installation Overview

